

CP-104EL-A

4-port RS-232 PCI Express serial board



- > PCI Express x1 compliant
- > 921.6 Kbps maximum baudrate for super fast data transmission
- > 128-byte FIFO and on-chip H/W, S/W flow control
- > Low profile form factor fits small-sized PCs
- > Drivers provided for Windows 7 x86/x64, XP/2003/Vista/2008 x86/x64, 2000, DOS, Linux 2.4/2.6, QNX 6, SCO Open Server 5/6, UnixWare 7
- > Easy maintenance with on-board LEDs and management software
- > 15 KV ESD protection on the board



: Overview

The CP-104EL-A is a smart, 4-port PCI Express board designed for POS and ATM applications. It is a top choice of industrial automation engineers and system integrators, and supports many different operating systems, including Windows, Linux, and even Unix. In addition, each of the board's 4 RS-232 serial ports supports a super

fast 921.6 Kbps baudrate. The CP-104EL-A provides full modem control signals to ensure compatibility with a wide range of serial peripherals, and its PCI Express "x1" classification allows it to be installed in any PCI Express slot.

: Smaller Form Factor

The CP-104EL-A is a low profile board that is compatible with any PCI Express slot. The board requires only a 3.3 VDC power supply, which

means that the board fits any host computer, ranging from shoebox to standard-sized PCs.

: Drivers Provided for Windows, Linux, and Unix

Moxa continues to support a wide variety of operating systems, and the CP-104EL-A board is no exception. Reliable Windows COM and Linux/Unix TTY drivers are provided for all Moxa boards, and other

operating systems, such as WEPOS, are also supported for embedded integration.

: Specifications

Hardware

Comm. Controller: 16C550C compatible

Bus: PCI Express x1

Connector: DB44 female

Serial Interface

Number of Ports: 4

Serial Standards: RS-232

Max. No. of Boards per PC: 4

Serial Line Protection

ESD Protection: 15 KV on the board

Performance

Baudrate: 50 bps to 921.6 Kbps

Serial Communication Parameters

Data Bits: 5, 6, 7, 8

Stop Bits: 1, 1.5, 2

Parity: None, Even, Odd, Space, Mark

Flow Control: RTS/CTS, XON/XOFF

Serial Signals

RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

Driver Support

Operating Systems: Windows 2000, Windows XP/2003/Vista/2008/7 x86/x64, DOS, Linux 2.4, 2.6 x86/x64, QNX 6, SCO Open Server 5/6, UnixWare 7

Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions: 67.21 x 103 mm (2.65 x 4.06 in)

Environmental Limits

Operating Temperature: 0 to 55°C (32 to 131°F)

Operating Humidity: 5 to 95% RH

Storage Temperature: -20 to 85°C (-4 to 185°F)

Regulatory Approvals

FCC: Part 15 Class B

EMS: EN55022, EN55024, EN61000-3-2, EN61000-3-3, EN61000-6-2, EN61000-6-4, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11

Power Requirements


Power Consumption: 805 mA @ 3.3 V

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

Dimensions



Ordering Information

Available Models

CP-104EL-A-DB9M: 4-port RS-232 PCI low profile Express x1 serial board (includes DB9 male cable)

CP-104EL-A-DB25M: 4-port RS-232 low profile PCI Express x1 serial board (includes DB25 male cable)

Package Checklist

- CP-104EL-A board
- DB9-M or DB25-M connection cable
- Standard bracket and low profile bracket
- Document and Software CD
- Quick Installation Guide (printed)
- Warranty Card

Connection Options (can be purchased separately)


CBL-M44M9x4-50

DB44 male to DB9 male x 4 (50 cm cable)



| PIN | RS-232 | PIN | RS-232 |
|-----|--------|-----|--------|
| 1 | DCD | 5 | GND |
| 2 | RxD | 6 | DSR |
| 3 | TxD | 7 | RTS |
| 4 | DTR | 8 | CTS |

DB9 male



CBL-M44M25x4-50

DB44 male to DB25 male x 4 (50 cm cable)



| PIN | RS-232 | PIN | RS-232 |
|-----|--------|-----|--------|
| 2 | TxD | 6 | DSR |
| 3 | RxD | 7 | GND |
| 4 | RTS | 8 | DCD |
| 5 | CTS | 20 | DTR |

DB25 male

